

General

| | |
|-----------------------|----------------------------|
| Ventilator Type | Natural Roof Ventilator |
| Base Dimensions | 580mm x 600mm |
| Dome Dimensions | 300mm w x 380mm d x 90mm h |
| Opening Diameter | 125mm, 150mm or 200mm |
| Ventilation Open Area | 29,040mm ² |
| Wind Loading | AS/NZS 4740 compliant |
| Bush Fire Rating | BAL-40 |

Material

| Component | Material | Dimensions |
|-------------------|-----------------------|----------------------------|
| Base | 0.6mm Aluminium | 580mm w x 600mm d |
| Dome | 1.0mm Stainless Steel | 300mm w x 380mm d x 90mm h |
| Seal | 2.0mm EPDM / silicone | 7mm w |
| 200mm Neck | 2mm ABS | 200mm d x 90mm h |
| 200-150mm Adapter | 2mm ABS | 150/200mm d x 90mm h |
| 150-125mm Adapter | 2mm ABS | 125/150mm d x 90mm h |
| Rivets | Aluminium | 0.3mm d |
| Strap | 1.0mm Aluminium | 210mm x 16mm |

Weight

| Component | Weight |
|-------------------|--------|
| Base | 1.45kg |
| 200mm Neck | 96g |
| 200-150mm Reducer | 47g |
| 150-125mm Reducer | 70g |



Applicable Product Codes

| Code | Description | Code | Description |
|---------|---------------|---------|-------------|
| RV568MM | Monument | RV568BS | Basalt |
| RV568SG | Shale Grey | RV568NS | Night Sky |
| RV568SM | Surfmist | RV568JP | Jasper |
| RV568DW | Dover White | RV568DN | Dune |
| RV568WG | Woodland Grey | RV568P | Paintable |

Compliance with the National Construction Code

When installed correctly, roof vents can be used to assist with compliance under National Construction Code (NCC 2022) provisions of 10.8.2 and 10.8.3.

Compliance with AS3959

When installed correctly, low profile roof vents are compliant with the fire rating requirements of AS3959-2009 up to BAL-40

Conditions of Storage, Maintenance and Use

Keep stored in a dry and cool area in the original packaging

Do not attempt repair or maintenance without contacting Partner Pacific

Limitations of Use

Designed for Class 1 and Class 10 construction in non-cyclonic regions

Not to be used for gas flueing

Do not use for exhausting hazardous or explosive materials

Do not use if the pitch of the roof is less than 10 degrees



5 Amay Crescent, Ferntree Gully Vic 3156
P | 03 9758 7844 F | 03 9758 7804
E | enquiries@partnerpacific.com